

TORQUE SPECIFICATION

Part Tightened	N-m	kgf-cm	ft-lbf
Brake line union nut	15	155	11
Bleeder plug	8.4	86	74 in.-lbf
Brake booster clevis lock nut	26	265	19
Stop lamp lock nut	26	265	19
Brake stroke sensor assy set bolt	9.3	95	82 in.-lbf
Brake pedal sub-assy set bolt	37	375	27
Brake pedal support assy x Body	13	130	9
Brake pedal support assy x Reinforcement	24	241	18
Brake master cylinder union No.1 set screw	1.8	18	16 in.-lbf
Brake master cylinder x Bracket	13	127	9
Brake actuator bracket x Tube bracket	5.0	51	44 in.-lbf
Cowl top panel sub-assy outer front	6.4	65	57 in.-lbf
Engine room R/B No.2 x Body	8.4	86	74 in.-lbf
Brake stroke simulator stud bolt	5.0	51	44 in.-lbf
Brake stroke simulator x Bracket	6.0	61	53 in.-lbf
Brake stroke simulator Bracket x Body	8.5	87	75 in.-lbf
Brake stroke simulator x Brake actuator tube assy	8.5	87	75 in.-lbf
Wheel nut	103	1,050	76
Front brake cylinder mounting x Steering knuckle	109	1,114	81
Front brake cylinder x Front brake cylinder mounting	34	347	25
Front brake cylinder x Flexible hose	33	337	24
Rear drum brake wheel cylinder x Backing plate	9.8	100	87 in.-lbf
Brake actuator assy x Brake actuator bracket No.2	18	184	13
Brake actuator assy x Gusset assy	7.5	76	66 in.-lbf
Brake actuator assy x Bracket	18	184	13
Brake actuator assy x Brake actuator damper	18	184	13
Brake actuator w/ gusset assy x Body	20	200	15
Brake actuator assy x Brake tube clamp bracket	5.0	51	44
Brake actuator x Brake actuator tube assy	8.5	87	75 in.-lbf
Brake actuator bracket x Front brake tube No.5 bracket	5.0	51	44 in.-lbf
Front speed sensor x Steering knuckle	8.0	82	71 in.-lbf
Front speed sensor wire harness clamp x Body Bolt A:	8.0	82	71 in.-lbf
Front speed sensor wire harness clamp x Shock absorber Bolt B:	19	192	14
Skid control ECU assy x Body	5.0	51	44 in.-lbf
Brake control power supply assy x Body	19	194	14
Yawrate sensor x Body	19	194	14