

TORQUE SPECIFICATION

Part Tightened	N-m	kgf·cm	ft·lbf
AIR CONDITIONING RADIATOR ASSY			
Air conditioning tube assy x Cooler evaporator sub-assy No. 1	3.5	35	30 in.·lbf
ELECTRIC INVERTER COMPRESSOR ASSY			
Electric inverter compressor assy x Engine	25	255	18
Suction hose sub-assy x Electric inverter compressor assy	9.8	100	87 in.·lbf
Discharge hose sub-assy x Electric inverter compressor assy	9.8	100	87 in.·lbf
W/ RECEIVER CONDENSER ASSY			
Cap x W/ receiver condenser assy	2.9	30	25 in.·lbf
W/ receiver condenser assy x Radiator	3.9	40	35 in.·lbf
Radiator support sub-assy upper RH x Radiator Bolt A	5.0	51	44 in.·lbf
Radiator support sub-assy upper RH x Radiator Bolt B	3.9	40	35 in.·lbf
Radiator support sub-assy upper RH x Radiator Bolt C	7.5	76	66 in.·lbf
Radiator support sub-assy upper LH x Radiator Bolt A	5.0	51	44 in.·lbf
Radiator support sub-assy upper LH x Radiator Bolt B	3.9	40	35 in.·lbf
Radiator support sub-assy upper LH x Radiator Bolt C	7.5	76	66 in.·lbf
Cooler refrigerant liquid pipe E x W/ receiver condenser assy	5.4	55	47 in.·lbf
Discharge hose sub-assy x W/ receiver condenser assy	5.4	55	47 in.·lbf