

ENGINE HOOD/DOOR

TORQUE SPECIFICATION

031W9-01

Part Tightened	N-m	kgf-cm	ft-lbf
HOOD			
Hood hinge x Hood	13	133	10
Hood hinge x Body	5.5	56	49 in. lbf
Hood lock x Hood	8.0	82	71 in. lbf
FRONT DOOR			
Door check x Body	30	306	22
Door check x Door panel	5.5	56	46 in. lbf
Door frame sub-assy rear lower x Door panel	8.0	82	71 in. lbf
Door glass x Front door window regulator	5.5	56	49 in. lbf
Door hinge x Body	26	265	19
Door hinge x Door panel	26	265	19
Door lock x Door panel	5.0	51	44 in. lbf
Door lock striker x Body	23	235	17
Door outside handle cover x Door panel	7.0	71	62 in. lbf
Door outside handle frame x Door panel	4.0	41	35 in. lbf
Outer view mirror x Door panel	10	102	7
Window regulator x Door panel	8.0	82	71 in. lbf
REAR DOOR			
Door check x Body	30	306	22
Door check x Door panel	5.5	56	49 in. lbf
Door hinge x Body	26	265	19
Door hinge x Door panel	26	265	19
Door lock x Door panel	5.0	51	44 in. lbf
Door lock striker x Body	23	235	17
Door outside handle cover x Door panel	4.0	41	35 in. lbf
Door outside handle frame x Door panel	7.0	71	62 in. lbf
Window division bar sub-assy x Door panel	5.5	56	49 in. lbf
BACK DOOR (LIFTBACK MODEL)			
Back door femaie stopper x Door panel	5.5	56	49 in. lbf
Back door hinge assy x Body	19.5	200	14
Back door hinge assy x Door panel	19.5	200	14
Back door lock assy x Door panel	8.0	82	71 in. lbf
Back door lock Striker x Body	11.5	120	8.0
Back door stay sub-assy x Body	7.0	71	62 in. lbf
Back door stay sub-assy x Door panel	22	224	16
Center stop lamp assy x Door panel	5.5	56	49 in. lbf