

TORQUE SPECIFICATION

Part Tightened		N-m	kgf-cm	ft-lbf
Oil pressure switch x Cylinder block		15	153	11
Stud bolt x Cylinder head		10	102	7.4
Oil pump assy x Cylinder head & block	Bolt A	32	326	24
	Bolt B	11	112	8.1
	Bolt C	11	112	8.1
	Nut D	24	245	18
	Bolt E	24	245	18
Camshaft timing oil control valve assy x Cylinder head		7.5	76	66 in. lbf
Engine mounting bracket x Cylinder block		55	561	41
Engine mounting bracket RH x Engine mounting insulator RH		52	530	38
Crankshaft damper x Crankshaft		128	1305	95
Cylinder head cover x Cylinder head		10	102	7.4
Ignition coil No. 1 x Cylinder head cover		9.0	92	80 in. lbf
Brake master cylinder reservoir cover x Cylinder head cover		9.0	92	80 in. lbf
Oil pan drain plug x Oil pan No.2		38	387	28
Oil pump cover x Oil pump assy	Bolt	8.8	90	78 in. lbf
	Screw	10	105	7.6
Windshield washer jar assy x Body	Bolt A	4.9	50	43 in. lbf
	Bolt B	14	143	10
	Nut	5.5	56	49 in. lbf
Reservoir bracket x Body		8.5	87	75 in. lbf
Brake master cylinder reservoir x Reservoir bracket and reservoir		8.5	87	75 in. lbf
Air cleaner assy x Cylinder head cover	Bolt	7.0	71	62 in. lbf
	Clamp	3.0	31	27 in. lbf
Battery negative terminal x Battery negative cable		6.0	61	53 in. lbf
Front wheel RH x Front axle		103	1050	76