

2AZ-FE FUEL

SERVICE DATA

Fuel pressure			304 to 343 kPa (3.1 to 3.5 kgf/cm ² , 44 to 50 psi)
Fuel injector	Resistance	at 20°C (68°F)	11.6 to 12.4 Ω
	Injection volume		76 to 92 cm ³ (4.6 to 5.6 cu in.) per 15 seconds
	Difference between each cylinder		16 cm ³ (1.0 cu in.) or less
	Fuel leakage		1 drop or less per 12 minutes
Fuel pump	Resistance	at 20°C (68°F)	0.2 to 3.0 Ω

SS

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Fuel delivery pipe x Cylinder head	20	204	15
Fuel tank vent tube set plate x Fuel tank	4.0	41	35 in.*lbf
No. 1 engine cover x Cylinder head cover sub-assembly	7.0	70	62 in.*lbf
Fuel pressure pulsation damper x Fuel delivery pipe	9.0	90	80 in.*lbf
Fuel tank filler pipe x Body	23.5	240	17
Filler pipe protector x Body	5.4	55	48 in.*lbf
Fuel tank band x Body	40	408	30
Fuel sender gauge assembly x Fuel tank	1.5	15	13 in.*lbf

SS