

INSPECTION

1. INSPECT WINDSHIELD WIPER MOTOR ASSEMBLY

(a) Check the LO operation.

- (1) Connect the battery's positive (+) lead to terminal 5 (+1) and the negative (-) lead to terminal 4 (E), and check that the motor operates at low speed (LO).

OK:

Motor operates at low speed (LO).

(b) Check the HI operation.

- (1) Connect the battery's positive (+) lead to terminal 3 (+2) and the negative (-) lead to terminal 4 (E), and check that the motor operates at high speed (HI).

OK:

Motor operates at high speed (HI).

(c) Check the automatic stop operation.

- (1) Connect the battery's positive (+) lead to terminal 5 (+1) and the negative (-) lead to terminal 4 (E). With the motor rotating at low speed (LO), disconnect terminal 5 (+1) to stop the wiper motor operation at any position other than the automatic stop position.
- (2) Using SST, connect terminals 1 (+S) and 5 (+1). Then connect the battery's positive (+) lead to terminal 2 (B) and the negative (-) lead to terminal 4 (E) to restart the motor operation at low speed (LO).



SST 09843-18040

- (3) Check that the motor stops automatically at the automatic stop position.

OK:

Refer to illustration.

If the result is not as specified, replace the motor assembly.




INSTALLATION

1. INSTALL WINDSHIELD WIPER MOTOR ASSEMBLY


- (a) Install the wiper motor with the 3 bolts.

Torque: 5.4 N*m (55 kgf*cm, 48 in.*lbf)




- (b) Align the matchmarks on the crank arm and motor.
- (c) Apply MP grease to the sliding parts of the wiper motor and the rod of the wiper link.
- (d) Connect the rod of the wiper link to the wiper motor.

2. INSTALL WINDSHIELD WIPER MOTOR AND LINK ASSEMBLY




- (a) Move the wiper motor and link in the direction shown by the arrow in the illustration to attach the wiper cushion to the body, and install the wiper motor and link.
- (b) Install the 2 bolts.
Torque: 5.5 N*m (56 kgf*cm, 49 in.*lbf)
- (c) Connect the connector.

3. INSTALL COWL TOP VENTILATOR LOUVER




- (a) Attach the 12 claws to install the louver.
- (b) Install the 2 clips.

4. INSTALL FRONT FENDER TO COWL SIDE SEAL LH




- (a) Attach the claw to install the front fender to cowl side seal.

5. INSTALL FRONT FENDER TO COWL SIDE SEAL RH




- (a) Attach the claw to install the front fender to cowl side seal.



6. INSTALL FRONT WIPER ARM AND BLADE ASSEMBLY RH

- Stop the wiper motor at the automatic stop position.
- Clean the wiper arm serration with a round file or equivalent.
- Clean the wiper pivot serration with a wire brush.



- Install the arm and blade with the nut. Make sure that the arm and blade comes to the position shown in the illustration.


Torque: 21 N*m (214 kgf*cm, 23 ft.*lbf)


HINT:

Hold down the arm hinge with your hand while tightening the nut.

7. INSTALL FRONT WIPER ARM AND BLADE ASSEMBLY LH

- Clean the wiper arm serration with a round file or equivalent.
- Clean the wiper pivot serration with a wire brush.





- (c) Install the arm and blade with the nut. Make sure that the arm and blade comes to the position shown in the illustration.

Torque: 21 N*m (214 kgf*cm, 23 ft.*lbf)

HINT:

Hold down the arm hinge with your hand while tightening the nut.

- (d) Operate the front wipers while spraying water or washer fluid on the windshield. Ensure that there is no interference between the blades and pillar.

8. INSTALL FRONT WIPER ARM HEAD CAP

- (a) Install the 2 caps.

9. CONNECT CABLE TO NEGATIVE BATTERY TERMINAL